

### Компактен Съединителен Съединител



Цвят на светлината



Stamps



\*The product is only available in markets without a valid patent for this model\*

## Техническа Спецификация

|  |  |  |                      |
|--|--|--|----------------------|
| <b>Product Code</b>                    | AC1-B7                                     | <b>Strip length</b>                      | 11 mm / 0.43 inch    |
| <b>Light Color</b>                     | Безцветно                                  | <b>Total number of connection points</b> | 2                    |
| <b>EAN Code</b>                        | 3800156660014                              | <b>Total number of potentials</b>        | 1                    |
| <b>Body Color</b>                      | transparent                                | <b>Type of wiring</b>                    | Side-entry wiring    |
| <b>Rated Current</b>                   | 32A  | <b>Width</b>                             | 13.1 mm / 0.516 inch |
| <b>Rated voltage</b>                   | 400V                                       | <b>Height</b>                            | 8.3 mm / 0.327 inch  |
| <b>Rated impulse voltage</b>           | 4kV  | <b>Depth</b>                             | 18.6 mm / 0.732 inch |
| <b>Connection technology</b>           | CAGE CLAMP®                                | <b>Flammability class per UL94</b>       | V2                   |
| <b>Actuation type</b>                  | Lever                                      | <b>Rated current UL (use group C)</b>    | 20A                  |
| <b>Connectable conductor materials</b> | Copper                                     | <b>Gross weight</b>                      | 0,002 kg             |
| <b>Nominal cross section</b>           | 4 mm <sup>2</sup>                          | <b>Net weight</b>                        | 0,002 kg             |
| <b>Solid conductor</b>                 | 0.2 ... 4 mm <sup>2</sup> / 24 ... 12 AWG  | <b>Warranty</b>                          | 2 Years              |
| <b>Fine-stranded conductor</b>         | 0.14 ... 4 mm <sup>2</sup> / 24 ... 12 AWG |  |                      |