



### LED Oberflächen Rundpanel CCT Farbwechsel



#### Leistung

18W

#### Lichtfarbe

Farbwechsel  
3000K-6000K

#### Stamps



## Technische Spezifikation

<b>Brand</b>	Optonica	<b>Material</b>	ALU+PC
<b>Product Code</b>	DL18-A3	<b>Operating Frequency</b>	50-60 Hz
<b>Power</b>	18W	<b>Temperature</b>	-20°C / +40°C
<b>Energy Consumption</b>	18 kWh/1000h	<b>Ra ≥</b>	80
<b>Input voltage</b>	AC165-265V	<b>Life span</b>	25 000 Hours
<b>Flux</b>	1450 lm	<b>Color Code</b>	CCT
<b>FLUX per watt</b>	80lm/W	<b>Body Color</b>	White
<b>IP</b>	44	<b>Lumen maintenance at end of service life</b>	70%
<b>Dimmable</b>	No	<b>Size of product</b>	φ226x35 mm
<b>Light Color</b>	Farbwechsel 3000K-6000K	<b>Size of package</b>	240x240x45 mm
<b>Wattage Equivalent</b>	100W	<b>Items per pack</b>	1
<b>EAN Code</b>	3800156625372	<b>Items per box</b>	20
<b>Energy Efficiency Label</b>	F	<b>Color Of The Shell</b>	White
<b>Beam angle</b>	100°	<b>Gross weight</b>	0,492 kg
<b>Power Factor</b>	0.95	<b>Net weight</b>	0,404 kg
<b>On/Off Cycles</b>	25 000x	<b>Warranty</b>	3 Years
<b>Instant On</b>	0.1s		