OPTONICA

DATASHEET



## Luce da Binario LED 12W 220V Bridgelux COB Chip Corpo Nero



**Potenza**

12W

**Colore della luce**

Luce naturale

**Stamps**

CE RoHS -80

## Specifiche tecniche

| | | | |
|---|---|---|---|
| **Brand** | Optonica | **On/Off Cycles** | 25 000x |
| **Product Code** | FL12-A2 | **Instant On** | 0.1s |
| **Power** | 12W | **Material** | Aluminium |
| **Energy Consumption** | 12 kWh/1000h | **Operating Frequency** | 50-60 Hz |
| **Input voltage** | AC220V | **Temperature** | -20°C / +40°C |
| **Flux** | 1200 lm | **Ra ≥** | 90 |
| **FLUX per watt** | 100lm/W | **Life span** | 25 000 Hours |
| **IP** | 20 | **Body Color** | Black |
| **Dimmable** | No | **Lumen maintenance at end of service life** | 70% |
| **Correlated Color Temperature** | 4000K | **Size of product** | Φ50x130mm |
| **Light Color** | Luce naturale | **Items per pack** | 1 |
| **EAN Code** | 3801057151014 | **Items per box** | 50 |
| **Energy Efficiency Label** | E | **Warranty** | 2 Years |
| **Beam angle** | 24° | | |