OPTONICA

DATASHEET



## Striscia LED 2835 Non Impermeabile



**Potenza**

4.8W/m

**Colore della luce**

Rosso

**Stamps**

CE RoHS -80

## Specifiche tecniche

| | | | |
|---|---|---|---|
| **Brand** | Optonica | **Material** | Flex PCB |
| **Product Code** | ST2835-A1 | **Operating Frequency** | 50-60 Hz |
| **Power** | 4.8W/m | **Temperature** | -20°C / +40°C |
| **Energy Consumption** | 4.8/m kWh/1000h | **Ra ≥** | 80 |
| **Input voltage** | DC12V | **Life span** | 25 000 Hours |
| **Flux** | 300 lm/m | **LED Type** | SMD |
| **FLUX per watt** | 300lm/W | **LEDs/m** | 60 |
| **IP** | 20 | **Roll** | 5 m |
| **Dimmable** | Yes | **Lumen maintenance at end of service life** | 70% |
| **Light Color** | Rosso | **Size of product** | 8 x 3mm |
| **EAN Code** | 3800156647046 | **Width** | 8 mm |
| **Energy Efficiency Label** | G | **Cutting distance** | 16.7mm |
| **Beam angle** | 120º | **Gross weight** | 0,043 kg |
| **Power Factor** | 0.5 | **Net weight** | 0,005 kg |
| **On/Off Cycles** | 25 000x | **Warranty** | 2 Years |
| **Instant On** | 0.2s | | |