





### Proiettore Lineare Magnetico a LED 48V 20W 4000K - M05



#### Potenza

20W

#### Colore della luce



#### Stamps



## Specifiche tecniche

|                                     |               |                                                 |               |
|-------------------------------------|---------------|-------------------------------------------------|---------------|
| <b>Brand</b>                        | Optonica      | <b>Instant On</b>                               | 0.1s          |
| <b>Product Code</b>                 | LN20-A7       | <b>Material</b>                                 | ALU+PC        |
| <b>Power</b>                        | 20W           | <b>Temperature</b>                              | -20°C / +40°C |
| <b>Energy Consumption</b>           | 20 kWh/1000h  | <b>Ra ≥</b>                                     | 90            |
| <b>Input voltage</b>                | DC48V         | <b>Life span</b>                                | 25 000 Hours  |
| <b>Flux</b>                         | 1200 lm       | <b>Body Color</b>                               | Black         |
| <b>FLUX per watt</b>                | 60 lm/W       | <b>Lumen maintenance at end of service life</b> | 70%           |
| <b>IP</b>                           | 20            | <b>Size of product</b>                          | 598x11x32mm   |
| <b>Dimmable</b>                     | No            | <b>Size of package</b>                          | 43x20x613mm   |
| <b>Correlated Color Temperature</b> | 4000K         | <b>Size of Box</b>                              | 630x220x345mm |
| <b>Light Color</b>                  | Luce naturale | <b>Items per pack</b>                           | 1             |
| <b>EAN Code</b>                     | 3801057153841 | <b>Items per box</b>                            | 50            |
| <b>Energy Efficiency Label</b>      | G             | <b>Series</b>                                   | M05           |
| <b>Beam angle</b>                   | 100°          | <b>Warranty</b>                                 | 2 Years       |
| <b>On/Off Cycles</b>                | 25 000x       |                                                 |               |