




### Lampione stradale LED 200W corpo grigio chip LUMILEDS IP65 75x130° - base NEMA



Potenza

200W

Colore della luce

 Luce fredda

Stamps



## Specifiche tecniche

|                                     |               |   |               |
|-------------------------------------|---------------|---|---------------|
| <b>Brand</b>                        | Optonica      | <b>Instant On</b>                               | 0.1s          |
| <b>Product Code</b>                 | SL200-A9      | <b>Material</b>                                 | Aluminium     |
| <b>Power</b>                        | 200W          | <b>Operating Frequency</b>                      | 50-60 Hz      |
| <b>Energy Consumption</b>           | 200 kWh/1000h | <b>Temperature</b>                              | -20°C / +40°C |
| <b>Input voltage</b>                | AC180-265V    | <b>Ra ≥</b>                                     | 80            |
| <b>Flux</b>                         | 26000 lm      | <b>Life span</b>                                | 50 000 Hours  |
| <b>FLUX per watt</b>                | 130 lm/W      | <b>Body Color</b>                               | GREY          |
| <b>IP</b>                           | 65            | <b>Lumen maintenance at end of service life</b> | 70%           |
| <b>Dimmable</b>                     | No            | <b>Size of product</b>                          | 226x590x156mm |
| <b>Correlated Color Temperature</b> | 6000K         | <b>Size of package</b>                          | 230x95x600mm  |
| <b>Light Color</b>                  | Luce fredda   | <b>Size of Box</b>                              | 614x493x486mm |
| <b>EAN Code</b>                     | 3800156692671 | <b>Items per pack</b>                           | 1             |
| <b>Energy Efficiency Label</b>      | E             | <b>Items per box</b>                            | 10            |
| <b>Beam angle</b>                   | 70°x135°      | <b>Warranty</b>                                 | 3 Years       |
| <b>On/Off Cycles</b>                | 50 000x       | <b>Adjustable Fixture Angle</b>                 | 0° - 90°      |