OPTONICA

DATASHEET



LED Super Slim Build-In+Surface Panel CCT



Power

30W

Light color

Color Changing 3000K-6000K

Stamps

CE RoHS -80

Technical Specification

Brand	Optonica	**Material**	ALU+PC
Product Code	DL30-A7	**Operating Frequency**	50-60 Hz
Power	30W	**Temperature**	-20°C / +40°C
Energy Consumption	30 kWh/1000h	**Ra ≥**	80
Input voltage	AC175-265V	**Life span**	25 000 Hours
Flux	3000 lm	**Color Code**	830-860
FLUX per watt	100lm/W	**Body Color**	White
IP	20	**Mount Type**	Reccesed/Surface
Dimmable	No	**Lumen maintenance at end of service life**	70%
Correlated Color Temperature	3000K-6000K	**Size of product**	ϕ330x19 mm
Light Color	Color Changing 3000K-6000K	**Size of package**	340x340x35 mm
Wattage Equivalent	200W	**Items per pack**	1
EAN Code	3800156625877	**Items per box**	10
Energy Efficiency Label	E	**Color Of The Shell**	White
Beam angle	100°	**Color Change Mode**	CCT
Hole Size	Φ65-310 mm	**Gross weight**	0,960 kg
Power Factor	0.9	**Net weight**	0,812 kg
On/Off Cycles	25 000x	**Warranty**	3 Years
Instant On	0.1s		