OPTONICA

DATASHEET



## LED SMD Portable Floodlight 1600 Lm 3 m Cable



**Power**

20W

**Light color**

White light

**Stamps**

## Technical Specification

| | | | |
|---|---|---|---|
| **Brand** | Optonica | **Operating Frequency** | 50-60 Hz |
| **Product Code** | FL20-A8 | **Temperature** | -20°C / +40°C |
| **Power** | 20W | **Ra ≥** | 80 |
| **Energy Consumption** | 20 kWh/1000h | **Life span** | 25 000 Hours |
| **Input voltage** | AC220-240V | **Color Code** | 860 |
| **Flux** | 1600 lm | **Lumen maintenance at end of service life** | 70% |
| **FLUX per watt** | 80 lm/W | **Size of product** | 245 x 260 x 180 mm |
| **IP** | 65 | **Size of package** | 255x75x260 mm |
| **Correlated Color Temperature** | 6000K | **Items per pack** | 1 |
| **Light Color** | White light | **Items per box** | 8 |
| **Wattage Equivalent** | 107W | **Material** | Aluminium |
| **EAN Code** | 3800156654037 | **Cable** | 3 m |
| **Energy Efficiency Label** | F | **Gross weight** | 1,338 kg |
| **Beam angle** | 120º | **Net weight** | 1,229 kg |
| **On/Off Cycles** | 25 000x | **Warranty** | 2 Years |
| **Instant On** | 0.1s | | |