


# OPTONICA

## DATASHEET



### LED Mini Panel Square Home Edition



#### Power

3W

#### Light color

White light

#### Stamps



RoHS



-80



## Technical Specification

|                                     |               |   |                |
|-------------------------------------|---------------|---|----------------|
| <b>Brand</b>                        | Optonica      | <b>Material</b>                                 | ALU+PC         |
| <b>Product Code</b>                 | DL3-B1        | <b>Operating Frequency</b>                      | 50-60 Hz       |
| <b>Power</b>                        | 3W            | <b>Temperature</b>                              | -20°C / +40°C  |
| <b>Energy Consumption</b>           | 3 kWh/1000h   | <b>Ra ≥</b>                                     | 80             |
| <b>Input voltage</b>                | AC185-260V    | <b>Life span</b>                                | 25 000 Hours   |
| <b>Flux</b>                         | 150 lm        | <b>Color Code</b>                               | 860            |
| <b>FLUX per watt</b>                | 50lm/W        | <b>Body Color</b>                               | White          |
| <b>IP</b>                           | 20            | <b>Lumen maintenance at end of service life</b> | 70%            |
| <b>Dimmable</b>                     | No            | <b>Size of product</b>                          | 90x90x21 mm    |
| <b>Correlated Color Temperature</b> | 6000K         | <b>Size of package</b>                          | 115x33x120 mm  |
| <b>Light Color</b>                  | White light   | <b>Size of Box</b>                              | 350x240x260 mm |
| <b>Wattage Equivalent</b>           | 10W           | <b>Items per pack</b>                           | 1              |
| <b>EAN Code</b>                     | 3800156624856 | <b>Items per box</b>                            | 40             |
| <b>Energy Efficiency Label</b>      | G             | <b>Gross weight</b>                             | 0,100 kg       |
| <b>Beam angle</b>                   | 120°          | <b>Net weight</b>                               | 0,075 kg       |
| <b>On/Off Cycles</b>                | 25 000x       | <b>Warranty</b>                                 | 2 Years        |
| <b>Instant On</b>                   | 0.1s          |   |                |