OPTONICA

DATASHEET



## LED SMD Floodlight Grey IP65




**Light color**

Neutral white

**Stamps**

## Technical Specification

| | | | |
|---|---|---|---|
| **Brand** | Optonica | **Material** | ALU + Glass |
| **Product Code** | FL150-B4 | **Operating Frequency** | 50-60 Hz |
| **Energy Consumption** | 150 kWh/1000h | **Temperature** | -20°C / +40°C |
| **Input voltage** | AC220-240V | **Ra ≥** | 80 |
| **Flux** | 15000 lm | **Life span** | 25 000 Hours |
| **FLUX per watt** | 100lm/W | **Color Code** | 845 |
| **IP** | 65 | **Body Color** | Gray |
| **Dimmable** | No | **LED Type** | SMD |
| **Correlated Color Temperature** | 4500K | **Lumen maintenance at end of service life** | 70% |
| **Light Color** | Neutral white | **Size of product** | 248.5x340x39 mm |
| **Wattage Equivalent** | 777W | **Items per pack** | 1 |
| **EAN Code** | 3800156657441 | **Items per box** | 5 |
| **Energy Efficiency Label** | E | **Cable** | 100cm, 3x0.75mm² black rubber cable |
| **Beam angle** | 90º | **Chip** | LUMILEDS 2835 |
| **Power Factor** | 0.9 | **Glass** | Lens |
| **Power LED** | 150W | **Gross weight** | 1,986 kg |
| **On/Off Cycles** | 25 000x | **Net weight** | 1,849 kg |
| **Instant On** | 0.1s | **Warranty** | 5 Years |