OPTONICA

DATASHEET




## LED SMD Floodlight IP65 White Body with Sensor



**Power**

30W

**Light color**

Warm white

**Stamps**

## Technical Specification

| | | | |
|---|---|---|---|
| **Brand** | Optonica | **Temperature** | -20°C / +40°C |
| **Product Code** | FL30-B3 | **Life span** | 25 000 Hours |
| **Power** | 30W | **Body Color** | White |
| **Energy Consumption** | 30 kWh/1000h | **LED Type** | SMD |
| **Input voltage** | AC180-265V | **Lumen maintenance at end of service life** | 70% |
| **Flux** | 2700 lm | **Size of product** | 159x178x30mm |
| **FLUX per watt** | 90lm/W | **Size of package** | 16.7x5x18.5cm |
| **IP** | 65 | **Size of Box** | 52.5x34.5x20.5cm |
| **Dimmable** | No | **Items per pack** | 1 |
| **Correlated Color Temperature** | 3000K | **Items per box** | 20 |
| **Light Color** | Warm white | **Cable** | 15 cm |
| **EAN Code** | 3801057158457 | **Detection Distance** | 8 M |
| **Energy Efficiency Label** | F | **Sensitivity angle** | 120 degree |
| **Beam angle** | 120º | **Gross weight** | 0,452 kg |
| **On/Off Cycles** | 25 000x | **Net weight** | 0,387 kg |
| **Instant On** | 0.1s | **Time Function** | 12sec-7min - adjustable |
| **Material** | ALU + Glass | **Warranty** | 2 Years |
| **Operating Frequency** | 50-60 Hz | | |