
OPTONICA

DATASHEET



## LED Linear High Bays 100W 6000K IP65 IK08



**Power**

100W

**Light color**

White light

**Stamps**

## Technical Specification

| | | | |
|---|---|---|---|
| **Brand** | Optonica | **Instant On** | 0.1s |
| **Product Code** | HB100-A2 | **Material** | Aluminium |
| **Power** | 100W | **Operating Frequency** | 50-60 Hz |
| **Energy Consumption** | 100 kWh/1000h | **Temperature** | -20°C / +40°C |
| **Input voltage** | AC220-240V | **Ra ≥** | 80 |
| **Flux** | 10000 lm | **Life span** | 25 000 Hours |
| **FLUX per watt** | 100lm/W | **Lumen maintenance at end of service life** | 70% |
| **IP** | 65 | **Size of product** | 603x118x92mm |
| **Dimmable** | No | **Size of package** | 590x90x137mm |
| **Correlated Color Temperature** | 6000K | **Items per pack** | 1 |
| **Light Color** | White light | **Items per box** | 5 |
| **EAN Code** | 3800156682535 | **Color Of The Shell** | Black |
| **Energy Efficiency Label** | E | **Color** | Black |
| **Beam angle** | 120°x60° | **Warranty** | 2 Years |
| **On/Off Cycles** | 25 000x | | |