

NOARK



Ex9UEP1+2 6.25 3P 1000

Stamps



Technical Specification

Brand	NOARK	Nominal voltage DC [V]	1000
EAN Code	8592765117595	System configuration DC	Yes
Mounting method	DIN rail (top hat rail) 35 mm	System configuration IT	No
Width in number of modular spacings	3	System configuration TN	No
Nominal voltage AC [V]	-	System configuration TN-C	No
Max. continuous voltage AC [V]	-	System configuration TN-C-S	No
Voltage protection level L-N [kV]	-	System configuration TN-S	No
Voltage protection level N-PE [kV]	-	System configuration TT	No
Construction size	3 modular spacing	System configuration other	Yes
Max. conductor cross section solid (solid, stranded) [mm ²]	25	Lightning impulse current (10/350 μs) [kA]	6.25
Max. conductor cross section flexible (fine-strand) [mm ²]	25	Max. continuous voltage DC [V]	1000
With remote signalling contact	No	Follow current extinguishing capability [kA]	-
Integrated backup fuse	No	Test class	Type 1 + 2
Signalling at the device	Optic	Exhausting	No
Power loss [W]	0.1	Energy-coordinated protection effect with regard to the terminal equipment	No

Number of poles (total)

3

Warranty

5 Years
