



LED-Hallenstrahler 50 W, 3CCT, IP65, mit 30 cm Kabel



Leistung

50W

Lichtfarbe

3CCT

Stamps



Technische Spezifikation

| | | | |
|-------------------------------------|-------------------|---|------------------|
| Brand | Optonica | Instant On | 0.1s |
| Product Code | HB50-B1 | Material | ALU+Optical Lens |
| Power | 50W | Operating Frequency | 50-60 Hz |
| Energy Consumption | 50 kWh/1000h | Temperature | -20°C / +40°C |
| Input voltage | AC180-265V | Ra ≥ | 80 |
| Flux | 6000 lm | Life span | 35 000 Hours |
| FLUX per watt | 120 lm/W | Body Color | Black |
| IP | 65 | Lumen maintenance at end of service life | 70% |
| Dimmable | No | Size of product | 177x177x54 mm |
| Correlated Color Temperature | 3000K/4000K/6000K | Size of package | 180x59x186 mm |
| Light Color | 3CCT | Size of Box | 374x312x398mm |
| EAN Code | 3800156682610 | Items per pack | 1 |
| Energy Efficiency Label | D | Items per box | 20 |
| Beam angle | 90° | Warranty | 3 Years |
| On/Off Cycles | 35 000x | | |