




### Panel LED de Superficie Redondo CCT Cambio de Color



#### Potencia

24W

#### Color de luz

Cambio de color 3000K-6000K

#### Stamps



RoHS



-80



## Especificación técnica

|                                |                             |   |               |
|--------------------------------|-----------------------------|---|---------------|
| <b>Brand</b>                   | Optonica                    | <b>Material</b>                                 | ALU+PC        |
| <b>Product Code</b>            | DL24-A3                     | <b>Operating Frequency</b>                      | 50-60 Hz      |
| <b>Power</b>                   | 24W                         | <b>Temperature</b>                              | -20°C / +40°C |
| <b>Energy Consumption</b>      | 24 kWh/1000h                | <b>Ra ≥</b>                                     | 80            |
| <b>Input voltage</b>           | AC165-265V                  | <b>Life span</b>                                | 25 000 Hours  |
| <b>Flux</b>                    | 2565 lm                     | <b>Color Code</b>                               | CCT           |
| <b>FLUX per watt</b>           | 107 lm/W                    | <b>Body Color</b>                               | White         |
| <b>IP</b>                      | 44                          | <b>Lumen maintenance at end of service life</b> | 70%           |
| <b>Dimmable</b>                | No                          | <b>Size of product</b>                          | φ245x35 mm    |
| <b>Light Color</b>             | Cambio de color 3000K-6000K | <b>Size of package</b>                          | 260x260x45 mm |
| <b>Wattage Equivalent</b>      | 145W                        | <b>Items per pack</b>                           | 1             |
| <b>EAN Code</b>                | 3800156625389               | <b>Items per box</b>                            | 20            |
| <b>Energy Efficiency Label</b> | E                           | <b>Color Of The Shell</b>                       | White         |
| <b>Beam angle</b>              | 100°                        | <b>Gross weight</b>                             | 0,567 kg      |
| <b>Power Factor</b>            | 0.95                        | <b>Net weight</b>                               | 0,468 kg      |
| <b>On/Off Cycles</b>           | 25 000x                     | <b>Warranty</b>                                 | 3 Years       |
| <b>Instant On</b>              | 0.1s                        |   |               |