



### Tubo LED T5 Enlazable - Plástico



Potencia

20W

Color de luz

 Luz blanca

Stamps



## Especificación técnica

|                                     |               |   |                 |
|-------------------------------------|---------------|---|-----------------|
| <b>Brand</b>                        | Optonica      | <b>Instant On</b>                               | 0.1s            |
| <b>Product Code</b>                 | TU20-A1       | <b>Operating Frequency</b>                      | 50-60 Hz        |
| <b>Socket</b>                       | T5            | <b>Temperature</b>                              | -20°C / +40°C   |
| <b>Power</b>                        | 20W           | <b>Ra ≥</b>                                     | 80              |
| <b>Energy Consumption</b>           | 20 kWh/1000h  | <b>Life span</b>                                | 25 000 Hours    |
| <b>Input voltage</b>                | AC220-240V    | <b>Color Code</b>                               | 860             |
| <b>Flux</b>                         | 1600 lm       | <b>LED Type</b>                                 | SMD             |
| <b>FLUX per watt</b>                | 80lm/W        | <b>Lumen maintenance at end of service life</b> | 70%             |
| <b>IP</b>                           | 20            | <b>Size of product</b>                          | 1450x28 mm      |
| <b>Dimmable</b>                     | No            | <b>Size of package</b>                          | 1490x30x25 mm   |
| <b>Correlated Color Temperature</b> | 6000K         | <b>Size of Box</b>                              | 1550x165x195 mm |
| <b>Light Color</b>                  | Luz blanca    | <b>Items per pack</b>                           | 1               |
| <b>Wattage Equivalent</b>           | 150W          | <b>Items per box</b>                            | 30              |
| <b>EAN Code</b>                     | 3800156655621 | <b>Material</b>                                 | Plastic         |
| <b>Energy Efficiency Label</b>      | F             | <b>Gross weight</b>                             | 0,217 kg        |
| <b>Beam angle</b>                   | 120°          | <b>Net weight</b>                               | 0,162 kg        |
| <b>Power Factor</b>                 | 0.9           | <b>Warranty</b>                                 | 2 Years         |
| <b>On/Off Cycles</b>                | 25 000x       |   |                 |