




### Mini pannello a LED Backlit Surface rotondo slim



#### Potenza

12W

#### Colore della luce



Luce fredda

#### Stamps



RoHS



-80



## Specifiche tecniche

<b>Brand</b>	Optonica	<b>Instant On</b>	0.1s
<b>Product Code</b>	DL12-B1	<b>Operating Frequency</b>	50-60 Hz
<b>Power</b>	12W	<b>Temperature</b>	-20°C / +40°C
<b>Energy Consumption</b>	12 kWh/1000h	<b>Ra ≥</b>	80
<b>Input voltage</b>	AC85-265V	<b>Life span</b>	25 000 Hours
<b>Flux</b>	840 lm	<b>Lumen maintenance at end of service life</b>	70%
<b>FLUX per watt</b>	70lm/W	<b>Size of product</b>	Φ160x28mm
<b>IP</b>	20	<b>Size of package</b>	17.5x3.5x17.5cm
<b>Dimmable</b>	No	<b>Size of Box</b>	37.5x36x37cm
<b>Correlated Color Temperature</b>	6000K	<b>Items per pack</b>	1
<b>Light Color</b>	Luce fredda	<b>Items per box</b>	10
<b>EAN Code</b>	3800156629783	<b>Material</b>	Aluminium
<b>Energy Efficiency Label</b>	G	<b>Gross weight</b>	0,187 kg
<b>Beam angle</b>	120°	<b>Net weight</b>	0,139 kg
<b>On/Off Cycles</b>	25 000x	<b>Warranty</b>	2 Years