

**NOARK**



**Ex9NL-N 3P+N C20 30mA**

Stamps

CE

RoHS

## Tehnička specifikacija

|  |                       |  |         |
|--|-----------------------|--|---------|
| <b>Brand</b>                               | NOARK                 | <b>Surge current capacity [kA]</b>   | 3       |
| <b>Product Code</b>                        | Ex9NL-N 3P+N C20 30mA | <b>Built-in depth [mm]</b>   | 77      |
| <b>IP</b>                                  | 20                    | <b>Concurrently switching N-neutral</b>  | Yes     |
| <b>EAN Code</b>                            | 8592765115157         | <b>Release characteristic</b>  | C       |
| <b>Frequency</b>                           | 50/60Hz               | <b>Number of protected poles</b>   | 3       |
| <b>Width in number of modular spacings</b> | 4                     | <b>Rated short-circuit breaking capacity I<sub>cn</sub> EN 60898 at 230 V [kA]</b> | 6       |
| <b>Power loss [W]</b>                      | 6.9                   | <b>Voltage type</b>  | AC      |
| <b>Number of poles (total)</b>             | 4                     | <b>Current limiting class</b>  | 3       |
| <b>Nominal rated voltage [V]</b>           | 400                   | <b>Over voltage category</b>   | 3       |
| <b>Nominal rated current [A]</b>           | 20                    | <b>Pollution degree</b>  | 2       |
| <b>Rated fault current [A]</b>             | 0.03                  | <b>Warranty</b>  | 5 Years |
| <b>Leakage current type</b>                | AC                    |  |         |