OPTONICA

DATASHEET



## Luminaire de plafond LED 12W CCT DIP-Switch IP20 Couverture Étoilée



**Puissance**

12W

**Couleur de lumiere**

CCT

**Stamps**

## echnical Specification

| | | | |
|---|---|---|---|
| **Brand** | Optonica | **On/Off Cycles** | 25 000x |
| **Product Code** | DL12-B1 | **Material** | Iron + PS |
| **Power** | 12W | **Operating Frequency** | 50-60 Hz |
| **Energy Consumption** | 12 kWh/1000h | **Temperature** | -20°C / +40°C |
| **Input voltage** | AC220-240V | **Ra ≥** | 80 |
| **Flux** | 880 lm | **Life span** | 25 000 Hours |
| **FLUX per watt** | 74 lm/W | **Lumen maintenance at end of service life** | 70% |
| **IP** | 20 | **Size of product** | Φ260x60mm |
| **Dimmable** | No | **Size of package** | 270x70x270mm |
| **Correlated Color Temperature** | 3000K/4000K/6000K | **Size of Box** | 560x370x290mm |
| **Light Color** | CCT | **Items per pack** | 1 |
| **EAN Code** | 3800156628328 | **Items per box** | 10 |
| **Energy Efficiency Label** | F | **Color** | Dotty Sparkle |
| **Beam angle** | 120º | **Warranty** | 2 Years |