
OPTONICA

DATASHEET



## Spot LED encastrable en saillie 10 W Noir 4000 K BRIDGELUX-CHIP




**Puissance**

10W

**Couleur de lumiere**

Lumière neutre

**Stamps**

## echnical Specification

| | | | |
|---|---|---|---|
| **Brand** | Optonica | **On/Off Cycles** | 25 000x |
| **Product Code** | OT1-A2 | **Instant On** | 0.1s |
| **Power** | 10W | **Material** | Aluminium |
| **Energy Consumption** | 10 kWh/1000h | **Operating Frequency** | 50-60 Hz |
| **Input voltage** | AC220-240V | **Temperature** | -20°C / +40°C |
| **Flux** | 800 lm | **Ra ≥** | 80 |
| **FLUX per watt** | 80lm/W | **Life span** | 25 000 Hours |
| **IP** | 20 | **Lumen maintenance at end of service life** | 70% |
| **Dimmable** | No | **Size of product** | ф100x65mm |
| **Correlated Color Temperature** | 4000K | **Size of package** | 110x110x80mm |
| **Light Color** | Lumière neutre | **Items per pack** | 1 |
| **EAN Code** | 3801057120010 | **Items per box** | 50 |
| **Energy Efficiency Label** | F | **Color Of The Shell** | Black |
| **Beam angle** | 90º | **Warranty** | 2 Years |