OPTONICA

DATASHEET



## 12W Panneau LED de surface rond 3CCT noir



**Puissance**

12W

**Couleur de lumiere**

CCT

**Stamps**

## echnical Specification

| | | | |
|---|---|---|---|
| **Brand** | Optonica | **On/Off Cycles** | 25 000x |
| **Product Code** | DL12-B1 | **Instant On** | 0.1s |
| **Power** | 12W | **Material** | Aluminium |
| **Energy Consumption** | 12 kWh/1000h | **Operating Frequency** | 50-60 Hz |
| **Input voltage** | AC85-265V | **Temperature** | -20°C / +40°C |
| **Flux** | 840 lm | **Ra ≥** | 80 |
| **FLUX per watt** | 70lm/W | **Life span** | 25 000 Hours |
| **IP** | 20 | **Lumen maintenance at end of service life** | 70% |
| **Dimmable** | No | **Size of product** | Φ145x29mm |
| **Correlated Color Temperature** | 3000K/4000K/6000K | **Size of package** | 165x30x165 mm |
| **Light Color** | CCT | **Items per pack** | 1 |
| **EAN Code** | 3801057129303 | **Items per box** | 100 |
| **Energy Efficiency Label** | G | **Warranty** | 2 Years |
| **Beam angle** | 120º | | |