

**NOARK**



### Surge Protective Device Ex9UE2 20 2P 275

Stamps



## Technical Specification

<b>IP</b>	20	<b>Voltage protection level N-PE [kV]</b>	-
<b>EAN Code</b>	8592765033529	<b>Short-circuit-proof</b>	Yes
<b>Color</b>	Grey	<b>Construction size</b>	2 modular spacing
<b>Mounting method</b>	DIN rail (top hat rail) 35 mm	<b>Max. conductor cross section solid (solid, stranded) [mm<sup>2</sup>]</b>	35
<b>Width in number of modular spacings</b>	2	<b>Max. conductor cross section flexible (fine-strand) [mm<sup>2</sup>]</b>	35
<b>System configuration</b>	TN-S, TT	<b>With remote signalling contact</b>	No
<b>Type of poles</b>	2	<b>Integrated backup fuse</b>	No
<b>Nominal discharge surge current (8/20) [kA]</b>	20	<b>Signalling at the device</b>	Optic
<b>Nominal voltage AC [V]</b>	275	<b>Category type 2</b>	Yes
<b>Max. continuous voltage AC [V]</b>	275	<b>Power loss [W]</b>	0.1
<b>Voltage protection level L-N [kV]</b>	1.4	<b>Warranty</b>	5 Years