OPTONICA

DATASHEET



Ex9UEP1+2 6.25 2P 1000

Stamps

echnical Specification

Brand	NOARK	**System configuration DC**	Yes
EAN Code	8592765117519	**System configuration IT**	No
Mounting method	DIN rail (top hat rail) 35 mm	**System configuration TN**	No
Width in number of modular spacings	2	**System configuration TN-C**	No
Nominal voltage AC [V]	-	**System configuration TN-C-S**	No
Max. continuous voltage AC [V]	-	**System configuration TN-S**	No
Voltage protection level L-N [kV]	-	**System configuration TT**	No
Voltage protection level N-PE [kV]	-	**System configuration other**	Yes
Construction size	2 modular spacing	**Lightning impulse current (10/350 µs) [kA]**	6.25
Max. conductor cross section solid (solid, stranded) [mm²]	25	**Max. continuous voltage DC [V]**	1000
Max. conductor cross section flexible (fine-strand) [mm²]	25	**Follow current extinguishing capability [kA]**	-
With remote signalling contact	No	**Specific energy (W/R) [kJ/Ohm]**	-
Integrated backup fuse	No	**Test class**	Type 1 + 2
Signalling at the device	Optic	**Exhausting**	No
Power loss [W]	0.1	**Energy-coordinated protection effect with regard to the terminal equipment**	No

Number of poles (total)	2
Nominal voltage DC [V]	1000

Warranty	5 Years