

NOARK



Ex9UEP1+2 6.25 2P 1000

Stamps



Technical Specification

Brand	NOARK	System configuration DC	Yes
EAN Code	8592765117519	System configuration IT	No
Mounting method	DIN rail (top hat rail) 35 mm	System configuration TN	No
Width in number of modular spacings	2	System configuration TN-C	No
Nominal voltage AC [V]	-	System configuration TN-C-S	No
Max. continuous voltage AC [V]	-	System configuration TN-S	No
Voltage protection level L-N [kV]	-	System configuration TT	No
Voltage protection level N-PE [kV]	-	System configuration other	Yes
Construction size	2 modular spacing	Lightning impulse current (10/350 μ s) [kA]	6.25
Max. conductor cross section solid (solid, stranded) [mm ²]	25	Max. continuous voltage DC [V]	1000
Max. conductor cross section flexible (fine-strand) [mm ²]	25	Follow current extinguishing capability [kA]	-
With remote signalling contact	No	Specific energy (W/R) [kJ/Ohm]	-
Integrated backup fuse	No	Test class	Type 1 + 2
Signalling at the device	Optic	Exhausting	No
Power loss [W]	0.1	Energy-coordinated protection effect with regard to the terminal equipment	No

Number of poles (total) 2

Nominal voltage DC [V] 1000

Warranty 5 Years
