



### Lampadaire LED 100 W, boîtier gris, puce LUMILEDS, IP65, angle de diffusion 75 x 130°, culot NEMA



#### Puissance

100W

#### Couleur de lumière

Lumière blanche

#### Stamps



RoHS



-80



## Technical Specification

<b>Brand</b>	Optonica	<b>Instant On</b>	0.1s
<b>Product Code</b>	SL100-A9	<b>Material</b>	Aluminium
<b>Power</b>	100W	<b>Operating Frequency</b>	50-60 Hz
<b>Energy Consumption</b>	100 kWh/1000h	<b>Temperature</b>	-20°C / +40°C
<b>Input voltage</b>	AC180-265V	<b>Ra ≥</b>	80
<b>Flux</b>	13000 lm	<b>Life span</b>	50 000 Hours
<b>FLUX per watt</b>	130 lm/W	<b>Body Color</b>	GREY
<b>IP</b>	65	<b>Lumen maintenance at end of service life</b>	70%
<b>Dimmable</b>	No	<b>Size of product</b>	186x475x157mm
<b>Correlated Color Temperature</b>	6000K	<b>Size of package</b>	190x95x486mm
<b>Light Color</b>	Lumière blanche	<b>Size of Box</b>	492x500x404mm
<b>EAN Code</b>	3800156692633	<b>Items per pack</b>	1
<b>Energy Efficiency Label</b>	E	<b>Items per box</b>	10
<b>Beam angle</b>	70°x135°	<b>Warranty</b>	3 Years
<b>On/Off Cycles</b>	50 000x	<b>Adjustable Fixture Angle</b>	0° - 90°