
OPTONICA

DATASHEET



## Panneau de Surface Rond LED AC85-260V




**Puissance**

6W

**Couleur de lumiere**

Lumière chaude

**Stamps**

CE RoHS -80

## echnical Specification

| | | | |
|---|---|---|---|
| **Brand** | Optonica | **On/Off Cycles** | 100 000x |
| **Product Code** | DL6-B1 | **Instant On** | 0.2s |
| **Power** | 6W | **Operating Frequency** | 50-60 Hz |
| **Energy Consumption** | 6 kWh/1000h | **Temperature** | -20°C / +40°C |
| **Input voltage** | AC85-265V | **Ra ≥** | 80 |
| **Flux** | 480 lm | **Life span** | 25 000 Hours |
| **FLUX per watt** | 80 lm/W | **Color Code** | 828 |
| **IP** | 20 | **Lumen maintenance at end of service life** | 70% |
| **Dimmable** | No | **Size of product** | ϕ120 x 38 mm |
| **Correlated Color Temperature** | 2800K | **Size of package** | 130x125x40 mm |
| **Light Color** | Lumière chaude | **Size of Box** | 420x270x285 mm |
| **Wattage Equivalent** | 48W | **Items per pack** | 1 |
| **EAN Code** | 3800156624030 | **Items per box** | 40 |
| **Energy Efficiency Label** | F | **Material** | Aluminium |
| **Beam angle** | 120º | **Gross weight** | 0,130 kg |
| **Power Factor** | 0.5 | **Net weight** | 0,101 kg |
| **Power LED** | 6W | **Warranty** | 2 Years |