



### Mini panneau rond à surface rétroéclairée par LED



#### Puissance

12W

#### Couleur de lumière

 Lumière neutre

#### Stamps



## Technical Specification

|                                     |                |   |                 |
|-------------------------------------|----------------|---|-----------------|
| <b>Brand</b>                        | Optonica       | <b>Instant On</b>                               | 0.1s            |
| <b>Product Code</b>                 | DL12-B1        | <b>Operating Frequency</b>                      | 50-60 Hz        |
| <b>Power</b>                        | 12W            | <b>Temperature</b>                              | -20°C / +40°C   |
| <b>Energy Consumption</b>           | 12 kWh/1000h   | <b>Ra ≥</b>                                     | 80              |
| <b>Input voltage</b>                | AC85-265V      | <b>Life span</b>                                | 25 000 Hours    |
| <b>Flux</b>                         | 840 lm         | <b>Lumen maintenance at end of service life</b> | 70%             |
| <b>FLUX per watt</b>                | 70lm/W         | <b>Size of product</b>                          | Φ160x28mm       |
| <b>IP</b>                           | 20             | <b>Size of package</b>                          | 17.5x3.5x17.5cm |
| <b>Dimmable</b>                     | No             | <b>Size of Box</b>                              | 37.5x36x37cm    |
| <b>Correlated Color Temperature</b> | 4500K          | <b>Items per pack</b>                           | 1               |
| <b>Light Color</b>                  | Lumière neutre | <b>Items per box</b>                            | 40              |
| <b>EAN Code</b>                     | 3800156629790  | <b>Material</b>                                 | Aluminium       |
| <b>Energy Efficiency Label</b>      | G              | <b>Gross weight</b>                             | 0,187 kg        |
| <b>Beam angle</b>                   | 120°           | <b>Net weight</b>                               | 0,139 kg        |
| <b>On/Off Cycles</b>                | 25 000x        | <b>Warranty</b>                                 | 2 Years         |