
OPTONICA

DATASHEET



## Mini pannello a LED Backlit Surface rotondo slim




**Potenza**

24W

**Colore della luce**

Luce fredda

**Stamps**

## Specifiche tecniche

| | | | |
|---|---|---|---|
| **Brand** | Optonica | **Instant On** | 0.1s |
| **Product Code** | DL24-B1 | **Operating Frequency** | 50-60 Hz |
| **Power** | 24W | **Temperature** | -20°C / +40°C |
| **Energy Consumption** | 24 kWh/1000h | **Ra ≥** | 80 |
| **Input voltage** | AC: 175-260V | **Life span** | 25 000 Hours |
| **Flux** | 1920 lm | **Lumen maintenance at end of service life** | 70% |
| **FLUX per watt** | 80 lm/W | **Size of product** | Φ280x29mm |
| **IP** | 20 | **Size of package** | 29.5x3.5x29.5cm |
| **Dimmable** | No | **Size of Box** | 37.5x30.5x31cm |
| **Correlated Color Temperature** | 6000K | **Items per pack** | 1 |
| **Light Color** | Luce fredda | **Items per box** | 10 |
| **EAN Code** | 3800156629844 | **Material** | Aluminium |
| **Energy Efficiency Label** | F | **Gross weight** | 0,433 kg |
| **Beam angle** | 120º | **Net weight** | 0,332 kg |
| **On/Off Cycles** | 25 000x | **Warranty** | 2 Years |