

NOARK



### Surge Protective Device Ex9UE2 20 3PN 275

Stamps



## Specificatii tehnice

|                                             |                               |                                                            |                   |
|---------------------------------------------|-------------------------------|------------------------------------------------------------|-------------------|
| Brand                                       | NOARK                         | Voltage protection level N-PE [kV]                         | 1.5               |
| IP                                          | 20                            | Short-circuit-proof                                        | Yes               |
| EAN Code                                    | 8592765033567                 | Construction size                                          | 4 modular spacing |
| Color                                       | Grey                          | Max. conductor cross section solid (solid, stranded) [mm²] | 35                |
| Mounting method                             | DIN rail (top hat rail) 35 mm | Max. conductor cross section flexible (fine-strand) [mm²]  | 35                |
| Width in number of modular spacings         | 4                             | With remote signalling contact                             | No                |
| System configuration                        | TN-S, TT                      | Integrated backup fuse                                     | No                |
| Type of poles                               | 3+N/PE                        | Signalling at the device                                   | Optic             |
| Nominal discharge surge current (8/20) [kA] | 20                            | Category type 2                                            | Yes               |
| Nominal voltage AC [V]                      | 275                           | Power loss [W]                                             | 0.1               |
| Max. continuous voltage AC [V]              | 275                           | Warranty                                                   | 5 Years           |
| Voltage protection level L-N [kV]           | 1.4                           |                                                            |                   |