

**NOARK**



### Surge Protective Device Ex9UE2 20 2P 275

Stamps



## Specificatii tehnice

|  |                               |  |                   |
|--|-------------------------------|--|-------------------|
| <b>IP</b>  | 20                            | <b>Voltage protection level N-PE [kV]</b>                                    | -                 |
| <b>EAN Code</b>                                    | 8592765033529                 | <b>Short-circuit-proof</b>   | Yes               |
| <b>Color</b>                                       | Grey                          | <b>Construction size</b>   | 2 modular spacing |
| <b>Mounting method</b>                             | DIN rail (top hat rail) 35 mm | <b>Max. conductor cross section solid (solid, stranded) [mm<sup>2</sup>]</b> | 35                |
| <b>Width in number of modular spacings</b>         | 2                             | <b>Max. conductor cross section flexible (fine-strand) [mm<sup>2</sup>]</b>  | 35                |
| <b>System configuration</b>                        | TN-S, TT                      | <b>With remote signalling contact</b>  | No                |
| <b>Type of poles</b>                               | 2                             | <b>Integrated backup fuse</b>  | No                |
| <b>Nominal discharge surge current (8/20) [kA]</b> | 20                            | <b>Signalling at the device</b>  | Optic             |
| <b>Nominal voltage AC [V]</b>                      | 275                           | <b>Category type 2</b>   | Yes               |
| <b>Max. continuous voltage AC [V]</b>              | 275                           | <b>Power loss [W]</b>  | 0.1               |
| <b>Voltage protection level L-N [kV]</b>           | 1.4                           | <b>Warranty</b>  | 5 Years           |