OPTONICA

DATASHEET

NOARK



Ex9UEP1+2 6.25 3P 1000

Stamps

Műszaki specifikáció

Brand	NOARK	**Nominal voltage DC [V]**	1000
EAN Code	8592765117595	**System configuration DC**	Yes
Mounting method	35 mm-es DIN-sínre szerelhető	**System configuration IT**	No
Width in number of modular spacings	3	**System configuration TN**	No
Nominal voltage AC [V]	-	**System configuration TN-C**	No
Max. continuous voltage AC [V]	-	**System configuration TN-C-S**	No
Voltage protection level L-N [kV]	-	**System configuration TN-S**	No
Voltage protection level N-PE [kV]	-	**System configuration TT**	No
Construction size	3 modul	**System configuration other**	Yes
Max. conductor cross section solid (solid, stranded) [mm²]	25	**Lightning impulse current (10/350 µs) [kA]**	6.25
Max. conductor cross section flexible (fine-strand) [mm²]	25	**Max. continuous voltage DC [V]**	1000
With remote signalling contact	No	**Follow current extinguishing capability [kA]**	-
Integrated backup fuse	No	**Test class**	Type 1 + 2
Signalling at the device	Optikai	**Exhausting**	No
Power loss [W]	0.1	**Energy-coordinated protection effect with regard to the terminal equipment**	No

Number of poles (total)	3
Warranty	5 év