




### Pannello LED Super Sottile Incassato+Superficie CCT



#### Potenza

18W

#### Colore della luce

Cambio colore  
3000K -  
6000K

#### Stamps



## Specifiche tecniche

<b>Brand</b>	Optonica	<b>Material</b>	ALU+PC
<b>Product Code</b>	DL18-A7	<b>Operating Frequency</b>	50-60 Hz
<b>Power</b>	18W	<b>Temperature</b>	-20°C / +40°C
<b>Energy Consumption</b>	18 kWh/1000h	<b>Ra ≥</b>	80
<b>Input voltage</b>	AC175-265V	<b>Life span</b>	25 000 Hours
<b>Flux</b>	1600 lm	<b>Color Code</b>	830-860
<b>FLUX per watt</b>	89lm/W	<b>Body Color</b>	White
<b>IP</b>	20	<b>Mount Type</b>	Recessed/Surface
<b>Dimmable</b>	No	<b>Lumen maintenance at end of service life</b>	70%
<b>Correlated Color Temperature</b>	3000K-6000K	<b>Size of product</b>	φ225x19 mm
<b>Light Color</b>	Cambio colore 3000K - 6000K	<b>Size of package</b>	235x230x35 mm
<b>Wattage Equivalent</b>	107W	<b>Items per pack</b>	1
<b>EAN Code</b>	3800156625860	<b>Items per box</b>	20
<b>Energy Efficiency Label</b>	F	<b>Color Of The Shell</b>	White
<b>Beam angle</b>	100°	<b>Color Change Mode</b>	CCT
<b>Hole Size</b>	Φ65-210 mm	<b>Gross weight</b>	0,470 kg
<b>Power Factor</b>	0.9	<b>Net weight</b>	0,342 kg

**On/Off Cycles**

25 000x

**Warranty**

3 Years

---

**Instant On**

0.1s

---