



### Plafoniera LED - Rotonda



#### Potenza

18W

#### Colore della luce

Cambio colore  
3000K -  
6000K

#### Stamps



## Specifiche tecniche

|                                     |                             |   |                |
|-------------------------------------|-----------------------------|---|----------------|
| <b>Brand</b>                        | Optonica                    | <b>Instant On</b>                               | 0.1s           |
| <b>Product Code</b>                 | DL18-B4                     | <b>Operating Frequency</b>                      | 50-60 Hz       |
| <b>Power</b>                        | 18W                         | <b>Temperature</b>                              | -20°C / +40°C  |
| <b>Energy Consumption</b>           | 18 kWh/1000h                | <b>Ra ≥</b>                                     | 80             |
| <b>Input voltage</b>                | AC220-240V                  | <b>Life span</b>                                | 25 000 Hours   |
| <b>Flux</b>                         | 1880 lm                     | <b>Lumen maintenance at end of service life</b> | 70%            |
| <b>FLUX per watt</b>                | 104 lm/W                    | <b>Size of product</b>                          | Φ220x51 mm     |
| <b>IP</b>                           | 54                          | <b>Size of package</b>                          | 225x58x225 mm  |
| <b>Dimmable</b>                     | No                          | <b>Size of Box</b>                              | 615x470x250 mm |
| <b>Correlated Color Temperature</b> | 3000K-6000K                 | <b>Items per pack</b>                           | 1              |
| <b>Light Color</b>                  | Cambio colore 3000K - 6000K | <b>Items per box</b>                            | 20             |
| <b>EAN Code</b>                     | 3800156625013               | <b>Gross weight</b>                             | 0,607 kg       |
| <b>Energy Efficiency Label</b>      | E                           | <b>Net weight</b>                               | 0,516 kg       |
| <b>Beam angle</b>                   | 120°                        | <b>Warranty</b>                                 | 2 Years        |
| <b>On/Off Cycles</b>                | 25 000x                     |   |                |