



### Proiettore LED SMD 150W corpo grigio IP65 con cavo da 100 cm



#### Potenza

150W

#### Colore della luce



Luce naturale

#### Stamps



RoHS



-80



## Specifiche tecniche

|                              |               |                                          |                   |
|------------------------------|---------------|------------------------------------------|-------------------|
| Brand                        | Optonica      | Instant On                               | 0.1s              |
| Product Code                 | FL150-A5      | Operating Frequency                      | 50-60 Hz          |
| Power                        | 150W          | Temperature                              | -20°C / +40°C     |
| Energy Consumption           | 150 kWh/1000h | Life span                                | 50 000 Hours      |
| Input voltage                | AC180-265V    | Body Color                               | GREY              |
| Flux                         | 15000 lm      | Lumen maintenance at end of service life | 70%               |
| FLUX per watt                | 100lm/W       | Size of product                          | 290 x 230 x 34 mm |
| IP                           | 65            | Size of package                          | 297x43x272mm      |
| Dimmable                     | No            | Size of Box                              | 450x309x293 mm    |
| Correlated Color Temperature | 4000K         | Items per pack                           | 1                 |
| Light Color                  | Luce naturale | Items per box                            | 10                |
| EAN Code                     | 3801057159089 | Material                                 | ALU+Glass         |
| Energy Efficiency Label      | E             | Cable                                    | 100 cm            |
| Beam angle                   | 90°           | Warranty                                 | 5 Years           |
| On/Off Cycles                | 50 000x       |                                          |                   |