

**NOARK**



### Residual Circuit Breaker with Overcurrent protection Ex9BL-N 1P+N C32 30mA

Stamps



RoHS



## Specifiche tecniche

<b>Brand</b>	NOARK	<b>Surge current capacity [kA]</b>	3
<b>Product Code</b>	Ex9BL-N 1P+N C32 30mA	<b>Built-in depth [mm]</b>	77
<b>IP</b>	20	<b>Concurrently switching N-neutral</b>	Yes
<b>EAN Code</b>	8592765076342	<b>Release characteristic</b>	C
<b>Frequency</b>	50/60Hz	<b>Number of protected poles</b>	1
<b>Width in number of modular spacings</b>	2	<b>Rated short-circuit breaking capacity I<sub>cn</sub> EN 60898 at 230 V [kA]</b>	6
<b>Power loss [W]</b>	6.5	<b>Voltage type</b>	AC
<b>Number of poles (total)</b>	2	<b>Current limiting class</b>	3
<b>Nominal rated voltage [V]</b>	230	<b>Over voltage category</b>	3
<b>Nominal rated current [A]</b>	32	<b>Pollution degree</b>	2
<b>Rated fault current [A]</b>	0.03	<b>Warranty</b>	5 Years
<b>Leakage current type</b>	AC		